


RECOMMENDED PCB LAYOUT

NOTES:

1. MAT'L HEADER
 PLASTICS: HIGH TEMPERATURE PLASTIC UL94V-0
 PIN : COPPER ALLOY
 EJECT MECHANISM
 GUIDE/BUTTON : HIGH THERMO PLASTIC UL94V-0
 PLATE : STEEL
 SIDE CONTACT : PHOS.BRONZE
 RING STAND : BRASS
2. DIMENSION "X"
 X=5.00mm : PIN No.1,17,34,35,51,68
 X=3.50mm : PIN No.36,67
 X=4.25mm : OTHERS
3. PLATING OF CONTACT:
 UNDER PLATING: Nickel ALL OVER
 CONTACT AREA: GOLD FLASH
 SOLDERING AREA: Tin-Lead
4. EJECT FORCE : 4.0kgf MAX.
5. CARD EJECT : 6mm
6. PUSH BUTTON COLOR : BLACK



MODEL		TAI-SOL ELECTRONICS CO. LTD.	
PART NAME	PCMCIA Conn. T/H TOP MOUNT	UNIT	mm
PART NO.	3.3/SV B.0 S/O.5.0mm	SCALE	1:1
TOL.	1.33-1450101-01	DATE	2004.03.25
MATERIAL	SEE NOTES	DWG. NO.	P11B5108A-03
FINISH	SEE NOTES	THE 3RD PROJECTION	

PCMCIA Conn. T/H TOP MOUNT	UNIT	mm
3.3/SV B.0 S/O.5.0mm	SCALE	1:1
1.33-1450101-01	DATE	2004.03.25
SEE NOTES	DWG. NO.	P11B5108A-03

CRITICAL	MAJOR
TOLERANCE	TABLE
XX	+0.25
XXX	+0.25
ANGLE	+0.10
	+2°